



Forcepoint Security Manager - PSM

Description

Connect securely to Forcepoint Security Manager

Vendor

This connection component is designed for secure connection to the following target:

Vendor	Forcepoint
Product	FSM
Product Category	Website
Product Versions	8.4+

CyberArk

This connection component works with the following CyberArk versions:

CyberArk Solution	Privileged Session Management
CyberArk Product	Privileged Session Manager (PSM)
CyberArk Versions	10.4 or higher
Artifact Version	1.0
Out of the Box	NO
Out of the Box in versions	

Support & Certification

Developed by	Bulwarx Ltd.
Certification Level	Community



- Business Confidential -

Prerequisites

The following prerequisites are required on the machine that will run this connection component :

- Follow the following procedure to set up your environment to use Google Chrome: [PSM for Web Applications](#)

Configuration

Connection Component Settings

Specify the following parameters at the connection component level:

Connection Component Root Level Parameters

Parameters that define generic settings of the PSM connection component.

Parameter Name	Description	Acceptable Values	Default Value
Id	A unique ID that identifies the connection component	String	PSM-ForcepointSM
DisplayName	The name to be displayed in the connection selection.	String	Forcepoint Security Manager



- Business Confidential -

Target Settings section

Parameters that define specific target machines settings. These parameters can be overridden at platform or account level.

Client Specific

Parameter Name	Description	Acceptable Values	Default Value
ActionTimeout	The maximum number of seconds to wait for an action to complete	Positive number	20
PageLoadTimeout	The maximum number of seconds to wait for a page to load	Positive number	30
BrowserPath	Path to the browser exe file	Full path	C:\Program Files (x86)\Google\Chrome\Application\chrome.exe
DriverFolder	Folder the drive is located.		C:\Program Files (x86)\CyberArk\PSM\Components
RunValidations	Specifies if the validations defined in WebFormFields run. If set to "Yes", validations are required.	Yes, No	Yes
EnableTrace	Specifies whether to enable debug mode on the component	Yes, No	No



- Business Confidential -

Web Form Settings

Parameter Name	Description	Acceptable Values	Default Value
LogonURL	The address of the web application. Specify the URL of the login page. The URL can include dynamic parameters such as the address that is replaced with the value of the corresponding property of the account.	URL	https://{address}:9443/manager
WebFormFields	Describes the list of login actions.	List of commands.	loginForm:idUserName>{Username} loginForm:idPassword>{Password} loginForm:idLoginButton>(Button) btnSettings>(Validation)(searchby=id) ptrMainProductBarSwitchButton>(Validation)(searchby=class)
EnforceCertificateValidation	Whether or not PSM will validate target website certificates when initiating PSM connections. This enables PSM to connect to local websites that do not have valid certificates, such as LAN applications with self-signed certificates.	Yes, No	No